PRODUCT PERFORMANCE VERIFICATION FOR HIGHLY CORROSIVE ENVIRONMENTS

Pauline Smith, US Army Research Laboratory and Starla Bickerstaff, Corrosion College

a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	Same as Report (SAR)	OF PAGES 15	RESPONSIBLE PERSON
16. SECURITY CLASSIFIC	17. LIMITATION OF	18. NUMBER	19a. NAME OF		
15. SUBJECT TERMS					
14. ABSTRACT					
13. SUPPLEMENTARY NOTES 2010 U.S. Army Corrosion Summit, Huntsville, AL, 9-11 Feb					
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				8. PERFORMING ORGANIZATION REPORT NUMBER	
				5f. WORK UNIT NUMBER	
				5e. TASK NUMBER	
4. TITLE AND SUBTITLE Product Performance Verification for Highly Corrosive Environments 6. AUTHOR(S)				5d. PROJECT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
				5b. GRANT NUMBER	
				5a. CONTRACT NUMBER	
1. REPORT DATE FEB 2010		2. REPORT TYPE		3. DATES COVERED 00-00-2010 to 00-00-2010	
maintaining the data needed, and c including suggestions for reducing	lection of information is estimated to ompleting and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding ar DMB control number.	ion of information. Send comments arters Services, Directorate for Info	s regarding this burden estimate or ormation Operations and Reports	or any other aspect of the 1215 Jefferson Davis	nis collection of information, Highway, Suite 1204, Arlington

Report Documentation Page

Form Approved OMB No. 0704-0188

Corrosion

- Costs of Corrosion \$270 Billion/Year
- There is no panacea where corrosion is concerned.
- There is no mathematical equation that will suggest an outcome.
- To be a product expert on all products is impossible; therefore individuals specifying in corrosive environments need to understand labels and listings to evaluate probability of success.

Product Performance versus Product Safety Compliance

- Traditional coating process in question due to stringent environmental regulations
- Hazardous emissions and waste generation are very costly
- Critical Coating Assessment:
 - Corrosion resistance, impact resistance, wet and dry adhesion will be used as basis to characterize and predict performance of coatings.

Importance of Independent Product Performance Verification

- Costly product/system failure and catastrophes can ensue where highly corrosive environments are concerned
- Product service life predictions and performance assessment are essential in determining how products will perform
- Why third-party evaluation of product performance is vital to making reliable specification decisions
- <u>Case Study</u> PVC-Coated Galvanized Steel Conduit

Understanding Coatings

- Proper Adhesion is absolutely necessary
- If bond is broken, corrosion problem remains hidden until swelled area becomes visible or problem occurs, such as failure of the item coated.
- In relation to PVC-coated Galvanized Rigid Conduit, we wanted to ensure the PVC adhered firmly to the GRC in the corrosive environments, in which it was being specified and installed to protect sensitive electrical and data wire.

History of PVC-Coated GRC


- All available products met exactly same UL 6 safety certification
 - The same safety certification met by all steel conduit, uncoated and coated
- Yet all products do not perform the same
- Accelerated Performance Testing needed to be established to help predict product service life in highly corrosive environments

- ETL-SEMKO developed an open standard for evaluating PVC-coated Galvanized Rigid Conduit based on:
 - Two ASTM tests for evaluating coating adhesion
 - 1. ASTM D870 Hot Water Immersion (200 hours)
 - 2. ASTM D1151 Exposure to Heat and Humidity (90 days)


- Heat and humidity testing was selected for several reasons:
 - 1. Universally accepted in the coating industry as standard parameters for evaluating how well a coating protects against corrosion.
 - 2. Acknowledged as corrosion-accelerating agents.
 - 3. When combined with real-time exposure, can be used to predict the product's lifecycle


• After 200-hour test, each product was tested for adhesion performance.

 Significant Differences were observed in adhesion performance of the four products.










PVC-Coating Failure in Hot Water Immersion Test after 50 hours (Conduit 4)





Results of adhesion success after approximately 50 hours in Hot Water Immersion

On left: Adhesion success of Conduit 1
On right: Adhesion success of Conduit 2

Results and Conclusion

- ETL testing and verification is based on actual product performance as a predictor of reliable service life.
- Open to any manufacturer to qualify
- On-going quarterly compliance verification
- ETL PVC-OO1



ETL Verified PVC-001

The PVC coating adhesion performance of this product has been ETL verified to the Intertek ETL SEMKO, High Temperature H₂O PVC Coating Adhesion, Test Procedure for 200 hours. Certificate Number: 3072346-004



Results and Conclusions

- No Performance Requirements for PVC-coated conduit in existing standards
- There is no mathematical equation to suggest an outcome.
- To be a product expert on all products is impossible; therefore individuals specifying in corrosive environments need to understand labels and listings to evaluate probability of success.

Questions?

Thank you for your time today.